



# Versilon™ TBOY Hose

## Polypropylene Braided Helically Convoluted Inner Tube Anti-Static Fluoropolymer Hose

Saint-Gobain Performance Plastics' Versilon TBOY hose is constructed with a black electrostatic dissipating conductive PTFE convoluted inner tube and reinforced with polypropylene braid. The convoluted inner tube has open pitch helical convolutions to ensure smooth product flow. The polypropylene braid resists abrasion better than stainless steel reinforcements and burn potential from accidental contact is greatly reduced.

Versilon TBOY hose's inner tube has a non-stick surface and cleans easily with steam, caustics, solvents or other cleaning agents. All standard sizes are fully vacuum rated at room temperature.

### Features and Benefits

#### PTFE inner tube:

- Excellent chemical resistance
- Compatible with almost all materials
- Rounded, open-pitch helical convolutions shaped to ensure smooth product flow
- Non-stick surface, easy to clean (steam, caustics, solvents or other cleaning agents)
- Easy to flex, yet won't flatten when bent

#### Polypropylene braid:

- Ultraviolet stabilized
- Offers good chemical resistance against many types of acids
- Resists abrasion better than stainless steel reinforcements
- Lightweight, with minimum force to bend
- Easy to transport, connect and disconnect
- Less strain on adjoining equipment/scales
- Braid fraying minimized, reducing risk of hand injuries from wire braid punctures
- Does not conduct internal heat as readily as stainless steel braided hoses
- Burn potential from accidental contact greatly reduced

### Typical Applications

- Sanitary transfer
- Solvent transfer
- Drain and sample lines
- Semi-transparent sight gauges
- Corrosive environments

### Regulatory Compliance

- USDA
- US Pharmacopeia Class VI

## TBOY Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Vacuum Hg @ 70°F		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(lb/ft)	(kg/m)
12TBOY	3/4	19.1	1-3/8	34.9	250	1.72	1,000	6.89	2.75	69.9	29.9	760	0.23	0.34
16TBOY	1	25.4	1-1/2	38.1	250	1.72	1,000	6.89	4.00	101.6	29.9	760	0.30	0.45
20TBOY	1-1/4	31.8	1-7/8	47.6	200	1.38	800	5.52	4.50	114.3	29.9	760	0.50	0.74
24TBOY	1-1/2	38.1	2-1/8	54.0	200	1.38	800	5.52	5.00	127.0	29.9	760	0.55	0.82
32TBOY	2	50.8	2-5/8	66.7	150	1.03	600	4.14	6.00	152.4	29.9	760	0.80	1.19
40TBOY	2-1/2	63.5	3-3/8	85.7	120	0.83	480	3.31	12.00	304.8	29.9	760	1.00	1.49
48TBOY	3	76.2	4	101.6	100	0.69	400	2.76	13.00	330.2	29.9	760	1.35	2.01
64TBOY	4	101.6	CF	CF	CF	CF	CF	CF	CF	CF	29.9	760	CF	CF

### ⚠ Important:

**Burst Pressure** ratings at ambient 70°F (21°C); see applicable notes below on vacuum/pressure ratings at temperatures other than ambient.

**Working Pressure** is given at room temperature. Decrease working pressure to 40 psig all sizes above 1/8" F.

**Vacuum Rating** all sizes = 29.9" Hg at 70°F. Decrease vacuum rating 1% for every 2°F above 150°F. 1-1/4" rated at 20" Hg; 1-1/2" rated at 24" Hg; 2" rated at 20" Hg when installed less than 2X minimum bend radius.

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies. CF = Consult factory.

## Construction

Inner Tube:	Black electrostatic dissipating conductive PTFE			
Reinforcement:	Polypropylene braid -Each strand of large diameter (denier) polypropylene monofilament is twisted and subsequently twined prior to braiding -Tested for maximum abrasion and chemical resistance -Tightly woven braid offers excellent abrasion resistance			
Temperature Rating:	-40°F to +250°F -40°C to +121°C			
Maximum Length:	3/4"	70'	2"	50'
	1"	65'	2-1/2"	30'
	1-1/4"	45'	3"	30'
	1-1/2"	70'	4"	20'

## Fitting Options

### Versilon Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)
- Flare-Thru fitting technology available:
  - 150 lb. lap-joint style flanged
  - Female cam and groove
  - Sanitary clamp style
  - 304 and 316 stainless steel flanges available

## Common Media

- General chemical transfer
- Hexane
- Caustic solutions

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Saint-Gobain Performance Plastics  
210 Harmony Road  
Mickleton, NJ 08056  
1-800-435-3992

www.processsystems.saint-gobain.com



NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Versilon™ is a trademark of Saint-Gobain Performance Plastics.